UC-7101/7110/7112 Series

RISC ready-to-run embedded computers with 1 or 2 serial ports, dual LANs, SD

- MOXA ART ARM9 32-bit 192 MHz processor
- 16 or 32 MB RAM
- 8 or 16 MB Flash ROM
- Dual or single10/100 Mbps Ethernet for network redundancy
- 1 or 2 software-selectable RS-232/422/485 ports
- 50 bps to 921.6 Kbps baudrate (non-standard baudrates supported)
- SD socket for storage expansion
- Built-in real-time clock (RTC) and buzzer
- Pre-installed Linux Kernel 2.6 platform
- -40 to 75°C wide temperature models available

Overview

The UC-7101/UC-7110/UC-7112 mini RISC-based communication platforms are ideal for embedded applications. The computers come with 1 or 2 RS-232/422/485 serial ports and single or dual 10/100 Mbps Ethernet LAN ports to provide users with a versatile communication platform.

The UC-7101/UC-7110/UC-7112 use the ARM9 RISC CPU. Its design architecture and modern semiconductor technology provide the CPU with a powerful computing engine and communication functions, but without generating too much heat. The built-in 8 or 16 MB NOR Flash ROM and 16 or 32 MB SDRAM provide plenty of storage, and the SD socket (UC-7101 and UC-7112 only) provide users with flexible storage expansion to run applications that generate a lot of data. The dual or single LAN ports built into the ARM9 make the UC-7101/7110/UC-7112 computers ideal communication platforms for data acquisition and protocol conversion applications, and the 1 or 2 RS-232/422/485 serial ports allow you to connect a variety of serial devices.

The pre-installed µClinux or Linux operating system provides an open platform for software development. This means that software written for desktop PCs can be easily ported to a UC-7101, UC-7110 or UC-7112 embedded computer with a GNU cross complier, eliminating the need to spend time modifying existing code. The operating system, device drivers, and your own software can all be stored in the UC-7101/UC-7110/UC-7112's flash memory.

Appearance

UC-7110/UC-7112



UC-7101



Hardware Specifications

Computer
CPU: MOXA ART ARM9 32-bit RISC CPU, 192 MHz
OS (pre-installed): µClinux or Linux
DRAM:
UC-7101/7110/7112: 16 MB
UC-7112 Plus: 32 MB onboard
Flash:
UC-7101/7110/7112: 8 MB onboard
UC-7112 Plus: 16 MB onboard

Storage
Storage Expansion: SD slot (UC-7101, UC-7112, and UC-7112 Plus only)

Ethernet Interface
LAN: Auto-sensing 10/100 Mbps (RJ45)
• UC-7101: 1 port
• UC-7110/7112/7112 Plus: 2 ports
Magnetic Isolation Protection: 1.5 KV built-in

Serial Interface
Serial Standards: RS-232/422/485 software-selectable (DB9 male)
• UC-7101: 1 port
• UC-7110/7112: 2 ports
ESD Protection: 15 KV ESD for all signals
Console Port: RS-232 (TxD, RxD, GND)
• UC-7101: 4-pin pin header output
• UC-7110/7112: 3-wire pin-header

Serial Communication Parameters
Data Bits: 5, 6, 7, 8
Stop Bits: 1, 1.5, 2
Parity: None, Even, Odd, Space, Mark
Flow Control: RTS/CTS, XON/XOFF, ADDC® (automatic data direction control) for RS-485
Baudrate: 50 bps to 921.6 Kbps (supports non-standard baudrates; see user's manual for details)

Serial Signals
RS-232: TxD, RxD, DTR, DSR, RTS, CTS, DCD, GND
RS-422: TxD+, TxD-, RxD+, RxD-, GND
RS-485-4w: TxD+, TxD-, RxD+, RxD-, GND
RS-485-2w: Data+, Data-, GND

LEDs
System: Ready
LAN: LED located on the RJ45 connector
• UC-7101: 10M/Link x 1, 100M/Link x 1
• UC-7110/7112: 10M/Link x 2, 100M/Link x 2
Serial:
• UC-7101: TxD x 1, RxD x 1
• UC-7110/7112: TxD x 2, RxD x 2

Physical Characteristics
Housing: Aluminum (1 mm)
Weight:
• UC-7101: 130 g
• UC-7110/7112: 190 g
Dimensions:
• UC-7101: 67 x 22 x 100.4 mm (2.64 x 0.87 x 3.95 in)
• UC-7110/7112: 77 x 111 x 26 mm (3.03 x 4.37 x 1.02 in)
Mounting: DIN-Rail, wall

Environmental Limits
Operating Temperature:
Standard Models: -10 to 60°C (14 to 140°F)
Wide Temp. Models: -40 to 75°C (-40 to 167°F)
Storage Temperature:
Standard Models: -20 to 80°C (-4 to 176°F)
Wide Temp. Models: -40 to 85°C (-40 to 185°F)
Ambient Relative Humidity: 5 to 95% (non-condensing)
Anti-Vibration: 1 g @ IEC-68-2-6, sine wave (resonance search), 5-500 Hz, 1 Oct/min, 1 cycle, 13 min 17 sec per axis (UC-7101/7110 only)

Power Requirements
Input Voltage: 12 to 48 VDC
Power Consumption: 4.5 W
• 170 mA @ 24 VDC
• 340 mA @ 12 VDC

Standards and Certifications
Safety:
• UC-7101: UL 60950, CSA-C22.2 No. 60950-1, EN 60950-1
• UC-7110/7112: UL 60950-1, CSA C22.2 No. 60950-1-03, EN 60950-1
EMC: EN 55022 Class A, EN 61000-3-2 Class A, EN 61000-3-3, EN 55024, FCC Part 15 Subpart B Class A
Green Product: RoHS, CRoHS, WEEE

Reliability
Alert Tools: Built-in buzzer and RTC (real-time clock)
Automatic Reboot Trigger: Built-in WDT (watchdog timer)
MTBF (mean time between failures):
UC-7101: 514,973 hrs
UC-7110: 149,414 hrs
UC-7112: 148,980 hrs

Warranty
Warranty Period: 5 years
Details: See www.moxa.com/warranty
Note: The Hardware Specifications apply to the embedded computer unit itself, but not to accessories. In particular, the wide temperature specification does not apply to accessories such as the power adaptor and cables.

Software Specifications

Linux

OS: Linux 2.6.9
File System: JFFS2, NFS, Ext2, Ext3
Internet Protocol Suite: TCP, UDP, IPv4, SNMPv1, ICMP, ARP, HTTP, CHAP, PAP, DHCP, NTP, NFS, SMTP, Telnet, FTP, TFTP, PPP, PPPoE
Internet Security: OpenVPN, iptables firewall
Web Server (Apache): Allows you to create and manage web sites; supports PHP and XML
Terminal Server (SSH): Provides secure encrypted communications between two un-trusted hosts over an insecure network
Dial-up Networking: PPP Daemon for Linux that allows Unix machines to connect to the Internet through dialup lines, using the PPP protocol, as a PPP server or client. Works with 'chat', 'dip', and 'diald', among (many) others. Supports IP, TCP, UDP, and (for Linux) IPX (Novell).
Watchdog: Features a hardware function to trigger system reset in a user specified time interval (Moxa API provided)
Application Development Software:
• Moxa API Library (Watchdog timer, Moxa serial I/O control, Moxa DI/DO API)
• GNU C/C++ cross-compiler
• GNU C library
• GDB source-level debugging server

µClinux

OS: µClinux 2.6.19
File System: JFFS2
Internet Protocol Suite: TCP, UDP, IPv4, SNMPv1, ICMP, ARP, HTTP, CHAP, PAP, DHCP, NTP, NFS, SMTP, Telnet, FTP, TFTP, PPP, PPPoE
Web Server (boa): Allows you to create and manage web sites
Terminal Server (Telnet): Provides telnet communications between two hosts over the network
Dial-up Networking: PPP Daemon for Linux allows Unix machines to connect to the internet through dialup lines, using the PPP protocol, as a PPP server or client. Works with 'chat', 'dip', and 'diald', among (many) others. Supports IP, TCP, UDP, and (for Linux) IPX (Novell)
Application Development Software:
• Moxa API Library (Watchdog timer, Moxa serial I/O control)
• arm-elf-gcc: C/C++ cross-compiler
• µClibc: POSIX standard C library

Dimensions

Unit: mm (inch)

UC-7110/UC-7112



UC-7101



Model Name	Serial Ports	LAN Ports	Storage	OS		Wide Temp.
	RS-232/422/485	10/100 Mbps	SD	uCLinux	Linux	
UC-7101	1	1	✓	✓	–	✓
UC-7110	2	2	–	✓	–	✓
UC-7112	2	2	✓	✓	✓	–

Ordering Information

Available Models

UC-7101-LX: Mini RISC-based embedded computer with 1 serial port, LAN, µClinux OS, -10 to 60°C operating temperature
UC-7110-LX: Mini RISC-based embedded computer with 2 serial ports, dual LANs, µClinux OS, -10 to 60°C operating temperature
UC-7112-LX: Mini RISC-based embedded computer with 2 serial ports, dual LANs, SD, µClinux 2.6 OS, -10 to 60°C operating temperature
UC-7112-LX Plus: Mini RISC-based embedded computer with 2 serial ports, dual LANs, SD, Linux 2.6 OS, -10 to 60°C operating temperature
UC-7101-T-LX: Mini RISC-based embedded computer with 1 serial port, LAN, µClinux OS, -40 to 75°C operating temperature
UC-7110-T-LX: Mini RISC-based embedded computer with 2 serial ports, dual LANs, µClinux OS, -40 to 75°C operating temperature

Package Checklist

- UC-7101 or UC-7110 or UC-7112 embedded computer
- Ethernet cable: RJ45 to RJ45 cross-over cable, 100 cm
- CBL-4PINDB9F-100: 4-pin pin header to DB9 female console port cable, 100 cm
- Universal power adaptor (including terminal block to power jack converter)
- Documentation and software CD
- Quick installation guide (printed)
- Warranty card

© Moxa Inc. All Rights Reserved. Updated Jul. 13, 2011. Specifications subject to change without notice. Please visit our website for the most up-to-date product information.